AQUA NC75 PLUS WAX

SECTION 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier AQUA NC75 PLUS WAX 1.2 Relevant identified uses of the substance or mixture and uses advised against **Cleaning Product** 1.3 Details of the supplier of the data sheet Travik Chemicals (UK) Limited Grindon Way Aycliffe Industrial Park Newton Aycliffe County Durham DL5 6SH United Kingdom info@travik.co.uk www.travik.co.uk Tel: 01325 307000 Fax: 01325 307070 1.4 Emergency telephone number

Nearest anti-poison centre or Guy's Hospital Poisons Unit, LONDON SE14 SER. (00 44)(1 71) 6 35 91 91 During normal opening times: 01325 307000 (08.30 - 16.30)

SECTION 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

- Eye irritation, category 2.
- Skin irritation, category 2.

2.2 Label Elements

In compliance with EC regulation No. 1272/2008 and its amendments. Pictogram(s):



Signal Word (s):

• WARNING Hazard Statement(s):

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

Precautionary Statement(s):

- P102 Keep out of reach of children.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard Statement(s):

None.

AQUA NC75 PLUS WAX

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Composition:				
Component	CAS	EINECS	CLP CLASS.	%
Sodium Metasilicate Pentahydrate	10213-79-3	229-912-9	Skin Corr. 1 B: H314. STOT SE 3: H335.	1-10%
Cocamidopropyl Betaine	61789-40-0	263-058-8	Eye Dam. 1: H318. Aquatic Chronic 3: H412.	1-10%
Alcohols C9 – 11 branched and linear,ethoxylated 5-20 EO	68439-46-3	N/A	Acute Tox. 4: H302. Eye Dam. 1: H318.	1-10%
Tetrasodium ethylenediamine tetraacetate	64-02-8	200-573-9	Met. Corr. 1: H290. Acute Tox. 4: H332. Skin Irrit. 2: H315. Eye Dam. 1: H318.	1-10%
Hydroxyethylidene -1,1,- diphosphonic acid, tetrasodium salt	29329-71-3	249-559-4	Acute Tox. 4: H302. Eye Irrit. 2: H319	1-10%
Alcohols, C12-C13-branched and linear, ethoxylated	160901-19-9	N/A	Acute tox. 4: H302. Eye Dam. 1: H318	1-5%
Amides, coco, N,N-bis(hydroxyethyl)	68603-42-9	271-657-0	Skin Irrit. 2: H315. Eye Dam. 1: H318	<5%
Coco/Soya fatty acid quaternised	68604-75-1	N/A	Acute Tox. 4: H302. Skin Irrit. 2: H315. Eye Dam. 1: H318. Aquatic Chronic 3: H412.	<5%
Amines, C12-14 (even numbered)-alkyldimethyl, N-Oxides	61788-90-7	931-341-1	Acute Tox. 4: H302. Skin Irrit. 2: H315. Eye Dam. 1: H318. Aquatic Acute 1: H400.	<5%
Propan-2-ol	67-63-0	200-661-7	Flam. Liq. 2: H225. Eye Irrit. 2: H319. STOT SE 3: H336.	<1%

See Section 16 for the full text of the R-phrases and H statements declared above.

SECTION 4. FIRST AID MEASURES

4.1 Description of first aid measures

Notes to the physician:

• No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

In the event of exposure by inhalation:

• Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

In the event of splashes or contact with eyes:

• Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

In the event of splashes or contact with skin:

• Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

In the event of swallowing:

• Immediately rinse mouth and provide fresh air. Get medical attention if any discomfort continues. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

- Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.
- Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.
- Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.

4.3 indication of any immediate medical attention and special treatment needed

No Data Available.

AQUA NC75 PLUS WAX

SECTION 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

• This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

5.2 Special hazards arising from the substance or mixture

• Aqueous liquid: does not show any particular risk in case of fire.

5.3 Advice for firefighters

- No specific fire fighting procedure given.
- Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

• Consult the safety measures listed under headings 7 and 8.

For non fire-fighters

- Avoid any contact with the skin and eyes.
- If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For fire-fighters

• Fire-fighters will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

• Collect as much as possible in a clean container for (preferable) reuse or disposal.

6.3. Methods and material for containment and cleaning up

- Flush remainder with water.
- 6.4. Reference to other sections
 - No data available.

SECTION 7. HANDLING AND STORAGE

- Requirements relating to storage premises apply to all facilities where the mixture is handled.
- Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

- Always wash hands after handling.
- Remove and wash contaminated clothing before re-using.

Recommended equipment and procedures:

- For personal protection, see section 8.
- Observe precautions stated on label and also industrial safety regulations
- Avoid skin and eye contact with this mixture.

Prohibited equipment and procedures:

• No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

• Store between 4°C and 25°C in a dry, well ventilated place.

Storage

• Keep the container tightly closed in a dry, well-ventilated place

Packaging

- Always keep in packaging made of an identical material to the original
- 7.3. Specific end use(s)

AQUA NC75 PLUS WAX

• The identified uses for this product are detailed in Section 1.2.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

Component	List	Туре	Value
Sodium Metasilicate Pentahydrate	UK WEL	TWA	2mg/m3

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Eye / face protection

• Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

- Skin Protection:

• When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

Hand protection

• Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

- Respiratory protection

 Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:	
Physical state:	Liquid
Colour	Clear, colourless
Odour	Slight, detergent
pH of the substance or preparation:	13.0 - 14.0
Flash point interval:	not relevant.
Vapour pressure:	not relevant.
Relative Density:	1.03
Water solubility:	Miscible in all proportions
9.2. Other information	

No data available.

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

- No dangerous reaction known under conditions of normal use.
- 10.2. Chemical stability
 - This mixture is stable under the recommended handling and storage conditions in section 7.
- 10.3. Possibility of hazardous reactions
 - No data available.

10.4. Conditions to avoid

• Active ingredient decomposes at elevated temperatures.

AQUA NC75 PLUS WAX

10. 5. Incompatible materials

• Keep away from: Strong oxidising agents, strong acids.

10.6. Hazardous decomposition products

• Decomposition products depend upon temperature, air supply and the presence of other materials.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Mixture:

• No toxicological data available for the mixture.

Skin corrosion/skin irritation:

- Causes skin irritation.
- Serious damage to eyes/eye irritation:
 - Causes serious eye irritation.

Respiratory or skin sensitisation:

Not determined.

Component Toxicology:

Component	Test	Туре	Value
Sodium Metasilicate Pentahydrate	Acute Oral Toxicity	LD50, Rat	1,280mg/kg
Cocamidopropyl Betaine	Acute Oral Toxicity	LD50, Rat	7,900mg/kg
Alcohols C9 – 11 branched and linear, ethoxylated 5-20 EO	Acute Oral Toxicity	LD50, Rat	>1,200mg/kg
Tetrasodium ethylenediamine tetraacetate	Acute Oral Toxicity	LD50, Rat	>2000mg/kg
Tetrasodium ethylenediamine tetraacetate	Inhalation	LC50, 4 h, Dust, Rat	1000-5000mg/kg
Hydroxyethylidene -1,1,-diphosphonic acid, tetrasodium salt	Acute Oral Toxicity	LD50, Rat	>2,850mg/kg
Hydroxyethylidene -1,1,-diphosphonic acid, tetrasodium salt	Skin Absorption	LD50, Rat	>5000mg/kg
Alcohols, C12-C13-branched and linear, ethoxylated	Acute Dermal Toxicity	LD50, Rat	>2,000mg/kg
Alcohols, C12-C13-branched and linear, ethoxylated	Acute Oral Toxicity	LD50, Rat	300-2,000mg/kg
Propan-2-ol	Acute Oral Toxicity	LD50, Rat	5,045mg/kg

SECTION 12. ECOLOGICAL INFORMATION

12.1. Toxicity

Component Ecotoxicology:

Component	Test	Туре	Value
Sodium Metasilicate Pentahydrate	Fish	96H LC50	3185mg/l
Sodium Metasilicate Pentahydrate	Daphnia	48H EC50	4857mg/l
Sodium Metasilicate Pentahydrate	Algae	96H EC50	>1000mg/l
Cocamidopropyl Betaine	Fish	96H LC50	2mg/l
Cocamidopropyl Betaine	Daphnia	48H EC50	6.5mg/l
Cocamidopropyl Betaine	Algae	96H EC50	1.84mg/l
Alcohols C9 – 11 branched and linear, ethoxylated 5-20	Fish	96H LC50	5 – 7mg/l
EO			
Alcohols C9 – 11 branched and linear, ethoxylated 5-20	Daphnia	48H EC50	5.1mg/l
EO			
Alcohols C9 – 11 branched and linear, ethoxylated 5-20	Algae	72H EC50	1.4 – 47mg/l
EO			

AQUA NC75 PLUS WAX

Component	Test	Туре	Value
Tetrasodium ethylenediamine tetraacetate	Fish	96H LC50	>100mg/l
Tetrasodium ethylenediamine tetraacetate	Daphnia	48H EC50	>100mg/l
Tetrasodium ethylenediamine tetraacetate	Algae	72H EC50	>100mg/l
Hydroxyethylidene -1,1,-diphosphonic acid, tetrasodium salt	Fish	96H LC50	368mg/l
Hydroxyethylidene -1,1,-diphosphonic acid, tetrasodium salt	Daphnia	48H EC50	527mg/l
Hydroxyethylidene -1,1,-diphosphonic acid, tetrasodium salt	Algae	72H EC50	9.16mg/l
Alcohols, C12-C13-branched and linear, ethoxylated	Fish	96H LC50	1 – 10mg/l
Alcohols, C12-C13-branched and linear, ethoxylated	Daphnia	48H EC50	1 – 10mg/l
Alcohols, C12-C13-branched and linear, ethoxylated	Algae	72H EC50	1 – 10mg/l
Amines, C12-14 (even numbered)-alkyldimethyl, N-Oxides	Fish	96H LC50	2.67 – 3.46mg/l
Amines, C12-14 (even numbered)-alkyldimethyl, N-Oxides	Daphnia	48H EC50	3.1mg/l
Amines, C12-14 (even numbered)-alkyldimethyl, N-Oxides	Algae	72H EC50	0.1428mg/l

12.2. Persistence and degradability

Component Ecotoxicology (Contd.)

• The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents

12.3. Bioaccumulative potential

- No data available.
- 12.4. Mobility in soil
 - No data available.

12.5. Results of PBT and vPvB assessment

• This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

• No know significant effects or critical hazards

SECTION 13. DISPOSAL CONSIDERATIONS

• Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Waste:

• Must be disposed of in accordance with local and national regulations.

Soiled packaging:

• Dispose of as normal industrial waste. If empty containers are recycled or disposed of, the receiver must be informed about possible hazards. NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14. TRANSPORT INFORMATION

Transport class: This product does not require a classification for transport.

AQUA NC75 PLUS WAX

SECTION 15. REGULATORY INFORMATION

- **15.1.** Safety, health and environmental regulations/legislation specific for the substance or mixture Particular provisions:
 - No data available.
- 15.2. Chemical safety assessment
 - No data available.

SECTION 16. OTHER INFORMATION

- Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.
- It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.
- The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.
- To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein
- Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist

Full Text of abbreviated H Statements:

- H225 Highly flammable liquid and vapour.
- H290 May be corrosive to metals.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H412 Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.